

# Models 325, 337 & 349 Electric Heated Asphalt Pan Product Data Sheet



Forrest electric heated asphalt pans are specifically designed to melt and apply asphalt (tar or bitumen) as an adhesive. Asphalt is used in built up blocks or insulation fittings, such as elbows and tees.

The motorized roller is partially submerged in the molten tar and allows the operator to safely and quickly apply a controlled thickness of tar to the workpiece.

The use of electric heating avoids the fire risk of gas fired melting pots.

Forrest Asphalt pans are available in three sizes.

### Features:

- Adjustable tar temperature
- Independent automatic pan shutoff prevents heating beyond 500° F.
- Control by simple on/off switch or automatic timer.
- Independently switched motorized roller.
- Double wall insulated body.
- Non-standard electrical configurations available.

Model	Roller Width (in)	Shipping Weight (lbs)	Shipping Dimensions (in)	Total Watts	Amp Draw		
					230 Volt 1 Ph	230 Volt 3 Ph	460 Volt 3 Ph
325	25	645	44 W x 70 L x 44 H	6750	30	17	9
337	37	820	44 W x 78 L x 46 H	11250	N/A	29	15
349	49	920	44 W x 89 L x 46 H	15750	N/A	40	20

Forrest Mfg. Co.  
2825 West 11<sup>th</sup> St. • Houston, Texas 77008  
Tel: 713-864-2545 • Fax: 713-864-3698  
Email: [info@forrestmfg.com](mailto:info@forrestmfg.com)  
[www.Forrestmfg.com](http://www.Forrestmfg.com)