

Model 308 Grinder/Router Product Data Sheet




The Model 308 is used to cut the inner diameter on piping insulation half rounds when the inner size is too small to cut using a bandsaw.

Uses specially developed grinding stones to cut all popular insulation materials, including cellular glass, plastic foams, fiber materials, and calcium silicate.

Adjustable rip fence and depth of cut allow inner diameters up to 3-1/2" centered on blocks up to 40" wide.

Grinding wheels not included.
Available individually or in sets.



Available Grinding Wheel Sizes		
Decimal	Pipe	Tube
.675	3/8	5/8"
.875	1/2	7/8"
1.050	3/4	
1.125		1-1/8"
1.315	1	
1.375		1-3/8"
1.660	1-1/4	
1.900	1-1/2	
2.125		2-1/8"
2.375	2	
2.875	2-1/2	
3.000		3"
3.125		3-1/8"
3.500		3-1/2"

Features:

- 2 Hp 3 phase 230 or 460 volt brake motor controlled with a magnetic starter.
- Dust catch funnel to direct produced dust to user provided dust collection system or catch box.

Shipping Information:

- Weight, Standard: 530 pounds
- Shipping Dimensions: 44" W x 69" L x 44" H

Forrest Mfg. Co.
2825 West 11th St. • Houston, Texas 77008
Tel: 713-864-2545 • Fax: 713-864-3698
Email: info@forrestmfg.com
www.Forrestmfg.com